


- Virtually indestructible 304 stainless steel
- Will not discolor or rust
- Resists abrasion, chemicals & UV
- Easy to install
- Cuts with shears or serrated scissors
- Halogen free



Specifications are subject to change without notice

**B04F**

Order No.	Nominal I.D.		Expansion Range Min. - Max.				Wall Thickness		PU		AWG of Ends	Carriers	Wires/Carrier	Total Ends	Weight Lbs/100'
	mm	in	mm	in	mm	in	mm	in	M	F					
B04-07F	6.4	1/4"	4.8	0.19	10.3	0.41	0.33	0.013	30	100	36	24	13	312	2.20
B04-10F	9.5	3/8"	6.4	0.25	15.9	0.63	0.33	0.013	30	100	36	48	7	336	2.54
B04-13F	12.7	1/2"	9.5	0.37	19.1	0.75	0.33	0.013	15	50	36	48	11	528	3.15
B04-20F	19.1	3/4"	12.7	0.50	31.8	1.25	0.33	0.013	15	50	36	48	15	720	6.90
B04-25F	25.4	1"	15.9	0.63	33.3	1.31	0.33	0.013	15	50	30	48	7	336	9.78
B04-32F	31.8	1-1/4"	19.1	0.75	44.5	1.75	0.33	0.013	15	50	30	48	10	480	13.70
B04-40F	38.1	1-1/2"	25.4	1.00	54.0	2.13	0.33	0.013	15	50	30	48	12	576	16.60