


A unique mixture of Polyolefin and Polyester yarns, is the ideal way to form the only shrinkable fabric of its kind. The woven construction makes this product extremely flexible and resistant to trapping water, heat and humidity. Provides outstanding abrasion, chafing and cutting protection, even at high temperatures.

Heatshrink fabric tubing is designed primarily to provide mechanical abrasion protection for components such as rubber hoses, plastic pipes, and harness wiring bundles. Also suitable for other applications, such as noise and rattle suppression.

- Shrink Temperature 176°F (80°C)
- Highly Flexible
- Halogen Free
- Excellent Chemical Resistance
- Superior Abrasion Resistance
- Over A Wide Temperature Range
- Cuts Easily With Scissors



| TYPE               | COLOUR    |
|--------------------|-----------|
| <b>MH2 0.48 BK</b> | <b>BK</b> |
| NW                 |           |



Specifications are subject to change without notice

| Order Number | Nominal Width | Minimum Diameter |      | Maximum Diameter |      | Weight  |          | Standard Spool Put-Ups |     |
|--------------|---------------|------------------|------|------------------|------|---------|----------|------------------------|-----|
|              | (NW)          | (mm)             | (in) | (mm)             | (in) | Kg/100m | Lbs/100' | (M)                    | (F) |
| MH20.48BK    | 1/2"          | 12.0             | 0.47 | 6.0              | 0.24 | 1.49    | 1.00     | 7.5                    | 25  |
| MH20.79BK    | 3/4"          | 20.0             | 0.79 | 10.0             | 0.39 | 2.23    | 1.50     | 7.5                    | 25  |
| MH21.18BK    | 1-3/16"       | 30.0             | 1.18 | 15.0             | 0.59 | 2.97    | 2.00     | 7.5                    | 25  |
| MH21.58BK    | 1-1/2"        | 40.0             | 1.57 | 20.0             | 0.79 | 3.72    | 2.50     | 7.5                    | 25  |