


MRF sleeving is the perfect choice for electronic and high tech applications where flame retardance and durability are primary concerns. Ease of installation makes it an efficient choice for long runs of wire or cable. The addition of an organic combustion inhibitor to our standard polyethylene terephthalate gives the sleeve an Underwriters Lab and CSA flame resistance rating of VW-1.



- VW-1 Approved
- Mil-202, FAR 25, FMVSS 302
- Economical and easy to install
- Cut and abrasion resistant
- Expands up to 150%
- Halogen free
- Resists gasoline and engine chemicals
- Available colours: Black with White Tracer (TB)  
White with Black Tracer (TW)  
Gray with White Tracer (GW)  
Spyder (SP) - Custom Color



TYPE	COLOUR
<b>MRF 2.00 TB .15</b>	
NW	PU



Specifications are subject to change without notice

Order Number	Nominal Width		Minimum Diameter		Maximum Diameter		Weight		Standard Spool Put-Ups	
	(NW)	(mm)	(in)	(mm)	(in)	Kg/100m	Lbs/100'	(M)	(F)	
MRF0.13TB.65	1/8	2.4	3/32	6.4	1/4	0.24	0.16	65	225	
MRF0.25TB.60	1/4	3.2	1/8	11.1	7/16	0.36	0.24	60	200	
MRF0.38TB.38	3/8	4.8	3/16	12.7	1/2	0.85	0.57	38	125	
MRF0.50TB.30	1/2	6.4	1/4	19.1	3/4	1.07	0.72	30	100	
MRF0.75TB.22	3/4	12.7	1/2	31.8	1 1/4	1.29	0.87	22	75	
MRF1.00TB.20	1	15.9	5/8	41.3	1 5/8	1.99	1.34	20	65	
MRF1.25TB.15	1 1/4	19.1	3/4	44.5	1 3/4	2.38	1.60	15	50	
MRF1.50TB.12	1 1/2	25.4	1	54.0	2 1/8	2.91	1.96	12	40	
MRF1.75TB.9	1 3/4	31.8	1 1/4	69.9	2 3/4	4.01	2.70	9	30	
MRF2.00TB.15	2	38.1	1 1/2	88.9	3 1/2	4.90	3.30	15	50	
MRF2.50TB.15	2 1/2	44.5	1 3/4	92.1	3 5/8	5.65	3.80	15	50	
MRF3.00TB.15	3	63.5	2 1/2	120.7	4 3/4	5.94	4.00	15	50	